The Sure Edge® Roof Trim System


Sure Edge is a fast-fit, high quality PVC-u edge trim system designed around a high quality finish and the durability to offer an extra long life. The trim is available in either black or white and comes complete with a PVC-u back plate that removes the need for a standard wooden batten. There is also a thinner back plate included which can be used to mount directly when a standard wooden batten is already in place.

Sure Edge® Drip Trim



- •Ensure Gutter Trim is completed before Check Kerb Trim.
- •Leave an expansion gap of 2.5mm between all lengths of trim
- •Fix a standard wooden batten to your fascia to extend the roof over the gutter.
- •Nail the smaller back plate directly on to the timber batten using ring nails provided.
- •Dress membrane down over the Built in Batten with a 75mm overhang.
- •Secure the Trim with 65mm poly top pins
- •Note: In areas of high wind, exposed areas and high buildings additional fixings between predrilled holes is recommended.

Sure Edge® Kerb Trim



- •Install the membrane with a 75mm overhang on all sides.
- •Hold the Trim in position and apply downward pressure to ensure a watertight seal.
- •Secure the Trim with 50mm Poly top pins through the pre-drilled fixing holes.
- •Note: If a secure fixing cannot be achieved a timber fixer should be fitted to the vertical edge of the roof.
- •In areas of high wind, exposed areas and high buildings additional fixings between predrilled holes is recommended.

Sure Edge® Corners & Clips

- •For all corner components simply apply super-glue to ONE edge and hold in place until set
- •Do not apply glue to both edges as the Trim needs to be able to expand and contract
- •The Check Kerb External Corner/Stop End have pop-out blanking plates indicated in black in the above diagram
- •To use as an external Check Kerb Trim corner remove both blanking plates
- •To use as a left hand or right hand Check Kerb Trim to Gutter Kerb Trim corner remove the corresponding blanking plate

Rubber4Roofs Ltd Phone: 02476 667 234 Free: 0800 313 4486 www.rubber4roofs.co.uk •The trim comes with joining clips that simply hook beneath the extrusion and clip over the top by applying positive pressure

