


Declaration of Performance – Liteslate

| | | | | |
|---|---|--|---|---|
| 1 | Unique identification code of the product type: | | LITESLATE | |
| 2 | Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4): | | Identification of each individual product is stated on the back of each panel and/or on the package labelling. | |
| 3 | Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | | For roof covering according to harmonised standard BS EN 492:2012 +A2:2018 | |
| 4 | Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11 (5): | | Britmet Tileform Ltd, Unit 8, Coneygree Industrial Estate, Coneygree Road, Tipton, West Midlands, DY4 8XP, United Kingdom | |
| 5 | Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): | | N/A | |
| 6 | System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: | | System 4 | |
| 7 | In case of the declaration of performance concerning a construction product covered by a harmonised standard: | | BS EN 492:2012 +A2:2018 | |
| 8 | Essential Characteristics | Performance | Notified Body | Harmonised Technical Specification |
| | Bending Moment: | 87Nm·m ⁻¹ | BBA | BS EN 492:2012 +A2:2018 |
| | Water Absorption: | 0.13% | | |
| | Water Immersion: | After 28 days warm water immersion at ambient temperature – not less than 75Nm·m ⁻¹ After 56 days warm water immersion at ambient temperature – not less than 75Nm·m ⁻¹ | | |
| | Heat/Aged: | After 28 days heat at ambient temperature – not less than 75Nm·m ⁻¹ After 56 days heat at ambient temperature – not less than 75Nm·m ⁻¹ | | |
| | Durability: | Excess of 20 years | BBA Clause 11 | |
| | External Fire Resistance: | BROOF(t4) (1) | Warrington Fire 19822L-Rev.2 | BS EN 13501-5:2016 |
| Heat/ Rain: | No visible cracks, delamination's or defects on the slates | | | |
| 9 | The performance of the product identified in points 1 and 2 conforms with the declared performance in point 8. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. | | | |
| Signed for and on behalf of the manufacturer by: | | | | |
|  | | | | |
| Joe Attley, Operations Director Britmet Tileform Ltd | | | | |

TD-DOPLITE-REV1

| | |
|-----------------|--------------|
| Created date: | 26/08/2025 |
| Approval Date: | |
| Effective date: | |
| Archive Date | |
| Approver: | Chris Powell |