



SAFETY DATA SHEET

2265 PU Adhesive

Page: 1
Compilation date: 09/12/2008
Revision date: 03/11/2017
Revision No: 8

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 2265 PU Adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Castle Composites Ltd

Units 1-5

Nisbet Way

Ravenstruther

ML11 7SF

United Kingdom

Tel: +44 (0) 1555 870 003

Fax: +44 (0) 1555 870 040

Email: sales@castlecomposites.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 7814 974642

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP:

Resp. Sens. 1B: H334; STOT RE 2: H373; Carc. 2: H351; Eye Irrit. 2: H319; Repr. 1B: H360D; Skin Irrit. 2: H315; Skin Sens. 1B: H317; -: EUH204

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. May damage the unborn child. May cause damage to organs through prolonged or repeated exposure. Contains isocyanates. May produce an allergic reaction.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

SAFETY DATA SHEET

2265 PU Adhesive

Page: 2

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351: Suspected of causing cancer.

[cont...]

H360D: May damage the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

EUH204: Contains isocyanates. May produce an allergic reaction.

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard



Signal words: Danger

Precautionary statements: P260: Do not breathe fumes.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Other hazards: Danger of serious damage to health by prolonged exposure.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	9016-87-9	-	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	10-30%

N-ETHYL-2-PYRROLIDONE

220-250-6	2687-91-4	-	Repr. 1B: H360D	1-10%
-----------	-----------	---	-----------------	-------

Section 4: First aid measures

4.1. Description of first aid measures

[cont...]

SAFETY DATA SHEET

2265 PU Adhesive

Page: 3

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Consult a doctor. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Evacuate the area immediately.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

[cont...]

SAFETY DATA SHEET

2265 PU Adhesive

Page: 4

disposal by an appropriate method. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.
Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m ³	0.07 mg/m ³	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Localised exhaust ventilation may be required in poorly ventilated areas.

Respiratory protection: An air-fed mask, or for short periods of work, a combination of charcoal filter and particulate filter is recommended. Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves. Nitrile gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

[cont...]

SAFETY DATA SHEET

2265 PU Adhesive

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale brown

Odour: Barely perceptible odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Reacts with water.

Viscosity: Viscous

Relative density: 1.14

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

ORL	RAT	LD50	49	gm/kg
SKN	RBT	LD50	>9400	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
--------	-------	-------

[cont...]

SAFETY DATA SHEET

2265 PU Adhesive

Page: 6

Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	-	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 05 01

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

[cont...]

SAFETY DATA SHEET

2265 PU Adhesive

Page: 7

Transport class: This product does not require a classification for transport.

[cont...]

SAFETY DATA SHEET

SOLFRE 2265

Page: 8

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH204: Contains isocyanates. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H360D: May damage the unborn child.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.