

Material Application

ONDULINE® APRON FLASHING is a corrugated apron flashing piece, designed to seal the gap between Onduline roofing sheets, and a vertical wall abutment for complete waterproofing and a seamless finish.

Application

- Ensures complete waterproofing at the wall abutment
- The ONDULINE® APRON FLASHING corrugated profile perfectly matches the Onduline CLASSIC and EASYLINE roof sheets.

Features & Benefits

- Complete waterproofing at the wall abutment
- Made from polypropylene (PPE) to withstand excess heat
- UV resistant for longlasting performance
- Installation is quick and easy.
- Suitable for any roof pitch

Technical characteristics

DIMENSIONS & WEIGHT

| | |
|----------------|---------------|
| Material | Polypropylene |
| Length (mm) | 930 |
| Width (mm) | 190 |
| Height (mm) | 80 |
| Weight (kg) | 0.35 |
| Thickness (mm) | 1.2 |

PACKAGING

| | |
|------------------------|-----------------|
| Pallet Qty | 500 |
| Pallet Weight (kg) | 206 |
| Carton Qty | 25 |
| Carton Weight (kg) | 9 |
| Carton Dimensions (mm) | 290 x 125 x 960 |



Color



Black

Warranty

All the claims will be considered with respect to application recommendations issued by Onduline company.

Installation

The product should be installed in accordance with the manufacturers' installation guidelines. For more details, please seek professional advice or contact enquiries@onduline.net.

This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/ distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company.

onduline.co.uk

150 Minories
Aldgate | London
EC3N 1LS