

Optimal Insulation Rolls 50/75/100mm Thickness



OPTIMAL – the best available solution for standard application

- Applications: ceiling, roof, walls, floors, outside insulation, sauna, acoustic ceiling, wood panel houses, log houses
- density 18 kg/m³, technology needed
- $\lambda = 0,0385$ W/m²K
- Support felt (inside) for fast fastening

As you unroll, the inner side is smoother
When installing, place this inner smoother side
Facing 'into' the room. This allows for better support.



Optimal Insulation Rolls 50/75/100mm Thickness



Optimal Insulation Rolls :for
Vertical and Horizontal Applications with
support felt for easy installation.



Optimal Insulation (18kg/m³) Thermal Conductivity 0.0385 W/m2k

Product Code	Length mm	Width mm	Thickness mm	Thickness ~Inches	Units/Pack Rolls	Area/Roll m ²	Area/Pack m ²
OPI18 380x50	9000	380	50	2	3	3.42	10.26
OPI18 380x75	6000	380	75	3	3	2.28	6.84
OPI18 380x100	6000	380	100	4	3	2.28	6.84
OPI18 570x50	9000	570	50	2	2	5.13	10.26
OPI18 570x75	6000	570	75	3	2	3.42	6.84
OPI18 570x100	6000	570	100	4	2	3.42	6.84

