

TECHNICAL DATA SHEET

SHED FELT

USE

This product can be used as an economical underlay or intermediate layer within a built-up felt roofing system. It can also be used as an underlay to bitumen shingles in a boarded pitch roof application.

PRODUCT INFORMATION

PolyesterPRO shed felt has a polyester fibre carrier as the core ingredient, rather than glass fibre. This significantly increases both tear and wear resistance as well as life expectancy of up to 15 years.

PERFORMANCE & COMPOSITION

Composition:	Bitumen
Form:	Roll
Finish:	Mineral: Black or Green
Length:	5m/8m/10m/20m
Width:	1m
Roll Weight:	10Kg/16Kg/20Kg/40Kg
Carrier:	Polyester



INSTALLATION

MATERIAL HANDLING:

Material should be unloaded and handled with care to avoid damages.

SITE STORAGE:

Material should be stored on end on a firm, level, clean base protected from direct sunlight.

PRIOR TO COMMENCEMENT:

Application must always follow good, safe working practice. Prior to commencing works it is advisable to assess the work area, irrespective of levels of competence, ensuring all works are being planned and undertaken in a safe, pragmatic manner. Temperature should be considered, with works being undertaken ideally at temperatures over 10°C. Avoid installing in wet or very cold weather.

PREPARATION:

Before starting on the roofing works, the installer should ensure the surfaces receiving the PolyesterPRO shed felt are sound, clean and dry. All existing old roof felt should be removed, and the roof structure should be checked for adequacy and strength prior to new works being carried out.

DURABILITY:

Life expectancy of this product is up to 15 years when installed as per manufacturers guidelines.

FIXING:

Extra Large Headed, Galvanised Clout Nails are recommended for installation.

INDEPENDENT ACCREDITATION



Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued